ShippingLabel

ShippingLabelID	int	<pk,fk1>		not null
ShippingTransactionID	int	<fk2>	<i9>	null
ShippingFulfillmentMethodID	int	<fk3>	<i4>	null
TrackingID	varchar(255)		<i1>	null
TrackingLink	varchar(255)			null
ProductCode	varchar(32)		<i2>	null
ShippingFulfillmentProductID	int	<fk7>	<i5>	null
LabelStatus	tinyint		<i3>	null
TotalWeight	float			null
WeightUnitID	int	<fk4>	<i6>	not null
Amount	money			null
CurrencyID	char(3)	<fk5>	<i8>	null
CouponCode	varchar(255)			null
Insurance	tinyint			null
ExpressDelivery	tinyint			null
PickupService	bit			not null
PickupDate	datetime			null
LabelDownloadURL	varchar(255)			null
EstimatedDeliveryDate	datetime			null
ActualDeliveryDate	datetime			null
ParcelLength	float			null
ParcelWidth	float			null
ParcelDepth	float			null
SizeUnitID	int	<fk6>	<i7>	not null
IsTestLabel	bit			not null

⊙╍ pk_shippinglabel   <pk>

▤	w_trackingid	<i1>
▤	w_productcode	<i2>
▤	i_labelstatus	<i3>
▤	i_fulfillmentmethodid	<i4>
▤	i_productid	<i5>
▤	w_weightunitid	<i6>
▤	w_sizeunitid	<i7>
▤	w_currencyid	<i8>
▤	i_shippingtransactionid	<i9>

OrderDocumentID = ShippingLabelID → **OrderDocument**

ShippingTransactionID = ShippingTransactionID

CurrencyID = CurrencyID

UnitID = SizeUnitID

UnitID = WeightUnitID

ShippingFulfillmentMethodID = ShippingFulfillmentMethodID

ShippingFulfillmentMethod

ShippingFulfillmentMethodID	int	<pk,fk1>		not null
ShippingFulfillmentTypeID	int	<fk2>	<i1>	null
IsInTestMode	bit			not null
WebserviceUsername	varchar(32)			null
WebservicePassword	varchar(32)			null
AutoGenerateLabels	bit			not null
ShopID	int	<fk3>	<i2>	not null

⊙╍ pk_shippingfulfillmentmethod   <pk>

▤	i_shippingfulfillmenttypeid	<i1>
▤	i_shopid	<i2>

ShopID = ShopID → **Shop**

UnitOfMeasurement

ShippingFulfillmentTypeID = ShippingFulfillmentTypeID

ShippingFulfillmentType

ShippingFulfillmentTypeID	int	<pk,fk1>		not null
SizeUnitID	int	<fk2>	<i1>	not null
WeightUnitID	int	<fk3>	<i2>	not null
MethodClassID	int			not null
ShippingTransactionClassID	int			not null
ShippingLabelClassID	int			not null
CanBatchAction	bit			not null
IntegrationType	varchar(20)			not null
Logging	bit			not null
WebserviceURL	varchar(255)			null
WebserviceTestURL	varchar(255)			null
AdminURL	varchar(255)			null
AdminTestURL	varchar(255)			null
RegistrationURL	varchar(255)			null
ExportDriver	varchar(255)			null
ImportHandler	varchar(255)			null
ExportFilename	varchar(50)			null

⊙╍ pk_shippingfulfillmenttype   <pk>

▤	w_sizeunitid	<i1>
▤	w_weightunitid	<i2>

UnitID = WeightUnitID

UnitID = SizeUnitID

ShippingTransaction

ShippingTransactionID	int	<pk,fk1>		not null
TransID	varchar(50)		<i2>	null
TransID2	varchar(50)		<i3>	null
TransStatus	varchar(50)			null
Amount	money			null
CurrencyID	char(3)	<fk2>	<i1>	null
ShippingFulfillmentTypeID	int	<fk3>	<i4>	not null
ShippingLabelsURL	varchar(255)			null
TransTime	datetime			null
TransTimeMod	datetime			null
IsTestTransaction	bit			not null

⊶ pk_shippingtransaction	<pk>
▤ i_currencyid	<i1>
▤ i_transactionnumber	<i2>
▤ i_transactionnumber2	<i3>
▤ i_shippingfulfillmenttypeid	<i4>

Currency

CurrencyID = CurrencyID

ShippingFulfillmentProductID = ShippingFulfillmentProductID

ShippingFulfillmentProduct

ShippingFulfillmentProductID	int	<pk>		not null
ShippingFulfillmentTypeID	int	<fk>	<i2>	null
ProductCode	varchar(32)		<i1>	not null

⊶ pk_shippingfulfillmentmethod	<pk>
▤ i_productcode	<i1>
▤ i_shippingfulfillmenttypeid	<i2>

ShippingFulfillmentTypeID = ShippingFulfillmentTypeID

ShippingFulfillmentTypeID = ShippingFulfillmentTypeID

DE_EPAGES::ExternalShipping	View: ExternalShipping
ePages 6.12	
Copyright © 2011 ePages GmbH	